

WATERLESS CLEANER™



Solvent Wood Floor Cleaner

Great For Tack Ragging!
Product #250

PRODUCT DESCRIPTION

Waterless Cleaner is a solvent-based cleaning compound designed specifically for cleaning and degreasing wood and concrete floor surfaces. Waterless Cleaner does a superb job of cleaning and degreasing prior to applying oil-modified urethane or other solvent-based finishes. Waterless Cleaner may also be used in the routine maintenance of wood and concrete surfaces. Waterless Cleaner is highly effective at dissolving oils, grease, hydraulic fluid, and removing black heel and tire marks. When used for maintaining wood floors, Waterless Cleaner eliminates the potential dangers of darkening and raised grain associated with water-based cleaners.

APPLICATION & MAINTENANCE

ROUTINE SWEEPING: Apply approximately two ounces of Waterless Cleaner on the dusting surface of a dry mop or similar sweeper. Allow mop to stand for thirty minutes. Sweep floor in the direction of the wood grain or length of the aisle. Shake out the dry mop at the end of each stroke.

HEAVY SOILING: For extremely dirty floors use four ounces of Waterless Cleaner on a dry mop, and apply as above. Waterless Floor Cleaner may also be applied with a string mop. Pour Waterless Cleaner into a wringer bucket, dampen a clean string mop with material, and wring out excess. Clean floor surface with a side to side sweeping motion. To remove black heel marks or spots, dampen a piece of cloth or blue scrubbing pad and wipe clean with a few strokes.

FLOOR FINISHING: Waterless Cleaner is also ideal for removing soiling and dust when applied to a tack rag prior to sealing floors. Equipment and applicators are easily cleaned with Waterless Cleaner, greatly reducing the problems and mess normally associated with cleanup following sealer application.

SPECIFICATIONS

Active Ingredients	Refined hydrocarbon distillates
Flash Point	105° F.
Color	Clear
Silicones	None
Mineral Oils	None
Separation	None
Stability	1 year minimum at room temperature
Weight Per Gallon	6.5 - 6.6

SAFETY INFORMATION

Health	1
Flammability	2
Reactivity	0
Personal Protection	B

DANGER: Harmful or Fatal if Swallowed. Contains Stoddard Solvent, CAS #8052-41-3. For external contact or contact with eyes, blot up material with a towel then flush with large volumes of clean water. If swallowed, drink olive oil, egg whites, or milk of magnesia. **Do Not Induce Vomiting. Call Physician Immediately. Avoid Prolonged or Repeated Contact.**

COMBUSTIBLE: Keep away from heat and open flame. Close container after each use. Provide adequate ventilation. Read MSD Sheet thoroughly before using.



605 Springs Road
Bedford, MA 01730
Telephone: 978.667.5161
Fax: 978.670.5797
www.perma.com