

PERMAKOTETM

Bowling Alley Wax



Available in clear, light oak and walnut!

A Quality Paste Wax
Product #700

PRODUCT DESCRIPTION

Designed to provide heavy-duty protection and a high gloss finish for all wood and some composition and stone surfaces, this smooth paste-type finish is formulated from select #1 carnauba and synthetic waxes suspended in a solvent-based system. Easily applied with a low-speed buffing machine and steel wool or buffing pad, this one-step application dissolves and suspends black heel marks, oily deposits, and soil, leaving behind a wax finish which can be buffed to a lustrous shine. Used in a routine maintenance program Permakote forms a tough film which will prevent damage to expensive wood surfaces from scratching, dirt penetration, and soil or water stains. Permakote also effectively protects cork, linoleum, terrazzo, marble and ceramic tile surfaces. Permakote is available in three colors; clear, light oak, or walnut, to allow varying degrees of grain enhancement when used on wood surfaces. Permakote is also effective in coating and protecting metal and fiberglass surfaces, and can be used as a release agent in molding or casting applications.

APPLICATION & MAINTENANCE

Sweep or vacuum floor surfaces to remove grit, sand, or dirt. Using a low-speed buffing machine (175-300 Rpm) apply a small amount of the paste wax to the bottom of a #2 steel wool or soft buffing pad. Using the buffing machine apply a very thin even coat of wax to the floor. For small areas, or those inaccessible with a buffing machine, the wax can be applied by hand using #2 steel wool, a soft cloth, pad, or brush. Permakote will dry to a satin sheen in approximately 15 or 20 minutes. The waxed surface can then be polished with a buffing machine and soft polishing brush, pad, or by hand with a soft cloth or brush to a hard, lustrous shine. Apply additional coats of wax until desired gloss and level of protection is obtained.

SPECIFICATIONS

Solids	18 - 20 %
Solvents	Petroleum distillates, gum turpentine
Flash Point	104° F
Drying Time	15 - 20 minutes
Color	Clear, light oak, dark brown
Weight Per Gallon	6.4 - 6.6
Coverage	700 ft ² /lb
Slip Resistance	0.5 minimum
VOC Content	685 grams/liter

SAFETY INFORMATION

Health	1
Flammability	2
Reactivity	0
Personal Protection	B

DANGER: Harmful or Fatal if Swallowed. Contains Stoddard Solvent CAS# 8052-41-3, and Gum Turpentine CAS# 8006-64-2. **If Swallowed, Do Not Induce Vomiting. Call Physician Immediately.**

COMBUSTIBLE: Keep away from heat and open flame. Close container after each use. Provide adequate ventilation. Read Material Safety Data Sheet thoroughly before using.



605 Springs Road
Bedford, MA 01730
Telephone: 978.667.5161
Fax: 978.670.5797
www.perma.com