

# WOOD CARE 101<sup>TM</sup>

## Solvent Liquid Wax



Available in clear, **light oak** and **walnut!**

**Protects and Shines  
Product #710**

### PRODUCT DESCRIPTION

Designed as a routine maintenance finish for all wood and some composition and stone surfaces, this viscous liquid finish is formulated from select waxes suspended in a solvent-based system. It's lower solids content minimizes buildup making it ideal for routine maintenance and gloss restoration programs. Easily applied with a low speed buffing machine and steel wool or polishing pad this one-step application dissolves and suspends black heel marks, oily deposits, and soil, leaving behind a wax finish which can be buffed to a lustrous shine. Used in a routine maintenance program Wood Care 101 forms a tough film which will prevent damage to expensive wood surfaces from scratching, dirt penetration, and soil or water stains. This premium finish also effectively protects linoleum, terrazzo, marble and ceramic tile surfaces. Wood Care 101 is available in three colors; clear, light oak, or walnut to allow varying degrees of grain enhancement when used on wood surfaces.

### APPLICATION & MAINTENANCE

Wood Care 101 may be used as is from the container, or if a more liquid consistency is desired the can may be placed on a radiator or placed in warm water for several minutes. Sweep or vacuum floor surfaces to remove grit, sand, or dirt. Using a low-speed buffing machine (175-300 Rpm) and a #2 steel wool or spray buffing pad, apply a small amount of the solvent liquid wax directly to the floor surface. Using the buffing machine spread a very thin even coat of wax on the floor. For small areas, or those inaccessible with a buffing machine, the wax can be applied by hand using #2 steel wool, a soft cloth, or lambs wool applicator. The wax will dry to a satin sheen in approximately 15 or 20 minutes. The waxed surface can then be polished with a buffing machine and soft polishing brush, polishing pad, or by hand with a soft cloth or brush to a hard, lustrous shine. Apply additional coats of wax until desired gloss and level of protection is obtained.

### SPECIFICATIONS

Solids	8 -10%
Solvents	Petroleum distillates, gum turpentine
Flash Point	104° F
Drying Time	15 - 20 minutes
Color	Clear
Weight Per Gallon	6.4 - 6.6
Coverage	1000 ft <sup>2</sup> /gallon
Slip Resistance	0.5 minimum

### SAFETY INFORMATION

Health	1
Flammability	2
Reactivity	0
Personal Protection	A

**DANGER: Harmful or Fatal if Swallowed.** Contains Stoddard Solvent CAS# 8052-41-3, and Gum Turpentine CAS# 8006-64-2. **If Swallowed, Do Not Induce Vomiting. Call Physician Immediately.**

**COMBUSTIBLE:** Keep away from heat and open flame. Close container after each use. Provide adequate ventilation. For complete information consult MSDS sheet.



605 Springs Road  
Bedford, MA 01730  
Telephone: 978.667.5161  
Fax: 978.670.5797  
www.perma.com