

HEAVY DUTY WAX

Water Based Carnauba Emulsion Floor Wax

Manufactured with pure #1 Grade Carnauba, this premium quality, self-polishing emulsion floor wax dries to a tough, lustrous shine with good slip resistance. Resilient enough to respond immediately to low-speed, dry, or spray buffing techniques, traffic and scuff marks can be easily repaired to restore the original shine. *Heavy Duty Wax* works especially well on linoleum and rubber tile floors which respond poorly to high-speed burnishing programs. Exceptionally versatile, *Heavy Duty Wax* also provides excellent results on concrete, stone, and sealed wood floors.



APPLICATION & MAINTENANCE

Best results are obtained when the finish is applied to floor surfaces that are 60° F. or warmer. Remove old finish or wax with one of Perma's premium quality strippers. Vacuum or mop up the stripping solution. If an alkaline stripper was used, rinse the floor thoroughly using 1 ounce of #127 *Tops* or *Easy Mix 1005* Neutral Cleaner per gallon of clean water (1:128). To obtain an acceptable level of appearance and gloss, a minimum three coats of finish is required. Optimum appearance and gloss will be obtained by applying 4-6 coats, depending on the porosity and type of flooring. Apply thin even coats allowing the finish to dry, depending on humidity and temperature, for approximately 30-45 minutes between coats. To recoat, wash the floor with #127 *Tops* Neutral Cleaner, or #129 *Super Blue* for heavier soil conditions, and allow it to dry. Apply thin even coats, allowing the finish to dry for approximately 30-45 minutes between coats. For daily maintenance, sweep and/or dry mop. Damp mop floors daily with #127 *Tops* or *Easy Mix 1005* Neutral Cleaner.

SPECIFICATIONS

Nonvolatile Solids	16 ± 0.6%
Total Active	20%
pH	8.5 - 9.5
Gloss 60°	80 @ 3 coats
Color	Light Amber
Weight Per Gallon	8.4 - 8.5
Slip Resistance (ASTM)	0.55 minimum
Stability	1 year minimum at room temperature
Freeze/Thaw Stability	3 cycles minimum
Drying Time	30- 45 minutes
Water Resistance	Excellent
Gallon Coverage (Feet ²)	2000 ± 10%
Removability (Gardner)	75 cycles maximum

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Read Material Safety Data Sheet thoroughly before using. This finish is not a hazardous mixture as defined in 29 CFR 1910.1200. Safety glasses and gloves should be worn during application and handling. **FIRST AID:** In the event of skin or eye contact, flush area with water for 15 minutes. In the event of eye irritation or ingestion, seek immediate medical treatment.



605 Springs Road, Bedford, MA 01730 USA
Tel: 978.667.5161, Fax: 978.670.5797
E-mail: Info@perma.com
www.perma.com